Chapter 6, Hash tables:

- General introduction; separate chaining (Today)
- Open addressing (next week Monday)
- Hash table performance (Monday after Thanksgiving)

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 -

Today:

- A few test 2 comments
- The story of the Map ADT
- Goals and terminology of the unit
- Separate chaining implementation
- Variables and metrics of performance

Find	Search the data structure for a given key				
Insert	Add a new key to the data structure				
Delete	Get rid of a key and fix up the data structure				

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

containsKey() Find

get() Find

put() Find + insert

remove() Find + delete

	Find	Insert	Delete
Unsorted array	$\Theta(n)$	$\Theta(1) \ [\Theta(n)]$	$\Theta(n)$
Sorted array	$\Theta(\lg n)$	$\Theta(n)$	$\Theta(n)$
Linked list	$\Theta(n)$	$\Theta(1)$	$\Theta(1)$
Balanced BST	$\Theta(\lg n)$	$\Theta(1) \ [\Theta(\lg n)]$	$\Theta(1) \ [\Theta(\lg n)$
What we want	$\Theta(1)$	$\Theta(1)$	$\Theta(1)$

▲□▶ ▲□▶ ▲三▶ ▲三▶ 三三 のへで





Open addressing:  $\frac{n}{m} < \alpha$  where  $\alpha < 1$ 



A	D	E	G	F	H	В	С	J	Ι	
A	D	Ε	G	F	H	В	С	J	Ι	
A	D	Е	G	F	Η	В	С	J	Ι	
A	D	Е	G	F	H	В	С	J	Ι	
A	D	Е	G	F	H	В	С	J	Ι	

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 の�?

Unit agenda:

Solution 1: Separate chaining (plus basic concepts and terminology). (Today)

◆□▶ ◆□▶ ◆三▶ ◆三▶ ○○ ○○○

- Solution 2: Open addressing. (Next week Monday)
- All about hash functions. (Next week Wednesday)
- Solution 3: Perfect hashing. (Monday after next)
- Looking carefully at performance. (Wednesday after next)

Hash table terminology:

- Hash table: A data structure, not an ADT ....
- Bucket: A position in the (main) array, or, abstractly, an index in the range [0, m].
- ► Hash function: A function from keys to buckets.
- Collision: When two keys are hashed to the same bucket.
- Chain: A sequence of keys that needs to be searched through to find a given key.

◆□▶ ◆□▶ ◆三▶ ◆三▶ ○○ ○○○

• Load factor ( $\alpha$ ): An upper bound on the ratio of keys to buckets.

Factors in best vs worst vs expected case:

- State of the table
- Length of the bucket
- Position of key in the bucket.

Parameters that can be adjusted for engineering a hash table:

▲ロト ▲圖ト ▲画ト ▲画ト 三回 - のへで

- Load factor  $\alpha$
- Rehash strategy
- Hash function

$$\begin{array}{cccc} O(1) & c_{0} \\ O(1) & c_{0} \\ O(1) & c_{0} \\ \vdots \\ O(1) & c_{0} \end{array} \end{array} \right\} \begin{array}{c} T(n) &= (n-1)c_{0} + c_{1} + c_{2}n \\ &= (c_{0} + c_{2})n + c_{1} - c_{0} \\ &= \Theta(n) \\ \vdots \\ O(1) & c_{0} \end{array} \right\}$$

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 臣 の�?

Hash functions should distribute the keys *uniformly* and *independently*.

Uniformity:

$$P(h(k)=i)=\frac{1}{m}$$

Independence:

$$P(h(k_1) = i) = P(h(k_1) = i | h(k_2) = j)$$

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへで

Coming up:

Do Optimal BST project (suggested by Monday, Nov 21)

```
Due Fri, Nov 18 (end of day)
Read Sections 7.(1 & 2)
Take quiz
```

```
Due Mon, Nov 21 (end of day)
Do Project 7.1 (as practice problem)
```

Due **Mon, Nov 28** (end of day) (recommended to be done before break) Read Section 7.3 Do Exercises 7.(4,5,7,8) Take quiz

▲ロト ▲圖ト ▲画ト ▲画ト 三回 - のへで